

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

PLEASE DO NOT BOOKMARK ANY ANYTIMECE WEBPAGES!

Our system will remember the last page you viewed when logging out and back in but please DO NOT exit out when taking a test. Your place will NOT be saved.

Please consider using the 2009 UPC Code Book.

How to take this non-illustrated course.

1. Download and Print the test questions.
2. Login to your account with your ID and password.
3. Viewing your status page, scroll down and click on "[Click here to start this course](#)".
4. Start viewing the code book. Refer to your printed test to find the correct answers. The questions track the code book.
5. As you find the answers, circle them on your printed copy.
6. At the end of each section, you'll enter the quiz which is the same as your printed test. Refer to your circled answers when actually answering the quiz on the web.
7. Upon passing, you will proceed to the next section. If you failed to pass, you will be moved to the beginning of that section for more review.

➤ ***Mobile users*** – *Many current mobile devices are compatible with AnytimeCE and will probably work. If not, use a desktop or laptop computer to complete your course.*

Quiz 1

Question 1: An airbreak is:

- a device used to stop the motion of a pipe threading machine
- a device used to stop the motion on a 1-ton or larger service vehicle
- a break in the line of a DVW system
- a physical separation which may be a low inlet into the indirect waste receptor from the fixture

Question 2: The correct reference for the above question is:

- 201.0
- 202.0
- 203.0
- 204.0

Question 3: An area drain:

- is a minimum of 2" in diameter
- must be made of ABS
- must be made of galvanized steel and be recessed 1/4" below grade
- is a receptor designed to collect surface or stormwater from an open area

Question 4: The correct reference for the above question is:

- 201.0
- 202.0
- 203.0
- 204.0

Question 5: An aspirator is:

- the handheld faucet on a flexible supply line, located on the basin of a sink
- a device on the outlet of a water faucet to entrain air into potable water
- a device supplied with water under positive pressure which passes through an integral orifice causing a vacuum
- a positive displacement pump apparatus whose single purpose is to inject chemicals for swimming pools

Question 6: The correct reference for the above question is:

- 201.0
- 202.0
- 203.0
- 204.0

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

Question 7: Backflow means:

- water running “uphill”
- the flow of water into the distributing pipes of a potable supply of water from any sources other than its intended source
- sewer water backing up into a basement during high runoff conditions
- hot water from a water tank heating up cold water lines

Question 8: The correct reference for the above question is:

- 201.0
- 202.0
- 203.0
- 204.0

Question 9: A battery of fixtures is:

- any group of two (2) or more similar, adjacent fixtures which discharge into a common horizontal waste or soil branch.
- any group of three (3) or more similar, adjacent fixtures which discharge into a common horizontal waste or soil branch.
- any group of four (4) or more similar, adjacent fixtures which discharge into a common horizontal waste or soil branch.
- any group of five (5) or more similar, adjacent fixtures which discharge into a common horizontal waste or soil branch.

Question 10: The correct reference for the above question is:

- 201.0
- 202.0
- 203.0
- 204.0

Question 11: An individual vent is installed to vent a fixture trap and:

- connects to the vent system above the fixture served, or terminates in the open air
- connects to the vent system below the fixture served, or terminates in the open air
- connects to the vent system at the same level as the fixture served or terminates in the open air
- all of the answers provided

Question 12: The correct reference for the above question is:

- 210.0
- 209.0
- 208.0

- 205.3
- 211.0

Question 13: What is clear water waste?

- waste water from a drinking fountain
- a sewer that is clear in color
- condensate from a boiler
- hot water rinse water from a commercial dishwasher
- all of the answers provided

Question 14: The correct reference for the above question is:

- 201.0
- 202.0
- 203.0
- 204.0
- 205.0

Question 15: What is a conductor?

- a pipe on the outside of a building which conveys stormwater from the roof to a stormwater drain
- a pipe on the inside of a building which conveys stormwater from the roof to a stormwater drain
- a pipe on the inside of a building which conveys waste water from the roof to a stormwater drain
- a pipe on the outside of a building which conveys waste water from the roof to a stormwater drain
- a pipe on the inside of a building which conveys waste water from the roof to a waste water drain

Question 16: The correct reference for the above question is:

- 201.0
- 202.0
- 203.0
- 204.0
- 205.0

Question 17: A Durham system is a design method for rainwater drains from buildings, which:

- uses threaded piping with recessed fittings
- is a method of heat recovery for boiler blowdown
- is not allowed by current code practice

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

Question 18: The correct reference for the above question is:

- 202.0
- 206.0
- 204.0
- 205.0
- 203.0

Question 19: An effective opening could best be described as:

- the minimum cross-sectional diameter of a circle of the water discharge
- the average cross-sectional diameter of a circle of the water discharge
- the maximum cross-sectional diameter of a circle of the water discharge
- 1.5 times the minimum cross-sectional diameter of a circle of the water discharge

Question 20: The correct reference for the above question is:

- 207.0
- 209.1
- 207.1
- 205.3

Question 21: Flammable vapor or fumes:

- occur when the flammable constituents in air exceed 10 % of the LFL
- occur when the flammable constituents in air exceed 10 % of the UFL
- occur when the flammable constituents in air exceed 25 % of the LFL
- occur when the flammable constituents in air are equal to 100 % of the LFL

Question 22: The correct reference for the above question is:

- 207.0
- 209.1
- 208.0
- 205.3

Question 23: A grade is:

- the slope of a pipe in reference to a horizontal line
- the fall of a pipe in reference to a horizontal line
- measured in a fraction of an inch per foot
- measured in a percentage of slope per foot
- all of the answers provided

Question 24: The correct reference for the above question is:

- 207.0
- 209.0
- 208.0
- 205.3
- 215.0

Quiz 2

Question 1: A horizontal pipe must be installed at an angle less than _____ degrees from the horizontal.

- 12-1/2
- 22-1/2
- 33-1/3
- 45
- 66-2/3

Question 2: The correct reference for the above question is:

- 210.0
- 209.0
- 208.0
- 205.3
- 215.0

Question 3: Which of the following conditions does the term "insanitary" NOT apply to?

- a trap that does not maintain its seal
- a toilet which does not have enough water to adequately flush the bowl
- a condition in which waste water could enter a potable water supply system
- a defective fixture
- NONE of the answers provided; all are insanitary conditions

Question 4: The correct reference for the above question is:

- 207.0
- 209.1
- 211.0
- 205.3

Question 5: Invert means:

- the highest portion of the outside of a horizontal pipe
- the lowest portion of the outside of a horizontal pipe
- the average mean distance of the outside of a horizontal pipe
- the lowest portion of the inside of a horizontal pipe
- none of the answers provided

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

Question 6: The correct reference for the above question is:

- 207.0
- 209.1
- 211.0
- 205.3

Question 7: In plumbing terms, a leader means:

- the end of a sewer snake that is used to break up clogs in waste lines
- the main waste vent that fixture side vents connect
- the water supply line that enters the building
- the drain pipe for conveying stormwater from a roof
- none of the answers provided

Question 8: The correct reference for the above question is:

- 214.0
- 209.1
- 211.0
- 205.3

Question 9: A macerating toilet system:

- connects to the toilet
- connects to other plumbing fixtures
- grinds and pumps the waste
- all of the answers provided except 1
- all of the answers provided

Question 10: The correct reference for the above question is:

- 214.0
- 209.1
- 211.0
- 215.0

Question 11: An offset is:

- a pipe that is 45 degrees from an other pipe
- a pipe that is 90 degrees from another pipe
- a pipe that is out of line but parallel with another pipe
- a pipe that is out of line and not parallel with another pipe
- none of the answers provided

Question 12: The correct reference for the above question is:

- 217.0
- 209.1
- 211.0
- 215.0

Question 13: PEX is:

- cross-linked polyethylene
- plastic external usage
- polyvinyl cross-linked material
- poly-propylene cross-linked material
- none of the answers provided

Question 14: The correct reference for the above question is:

- 216.0
- 218.0
- 211.0
- 215.0

Question 15: A riser is:

- a water supply pipe which extends vertically one (1) full story or more to convey water to branches or fixtures
- a vent system which extends vertically one (1) full story or more for venting of the waste system
- a waste system conductor which is located vertically one (1) full story or more above the main waste conductor
- all of the answers provided
- none of the answers provided

Question 16: The correct reference for the above question is:

- 216.0
- 220.0
- 211.0
- 215.0
- 205.0

Question 17: A sump is:

- an approved tank which receives liquid waste, which is located above the normal grade, and which must be emptied by mechanical means
- an approved tank which receives liquid waste, is located below the normal grade, and which must be emptied by mechanical means
- any tank which receives liquid waste, is located below the normal grade, and which must be emptied by mechanical means
- an approved tank which receives liquid waste, is located below the normal grade, and which must not be emptied by mechanical means
- none of the answers provided

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

Question 18: The correct reference for the above question is:

- 216.0
- 220.0
- 221.0
- 215.0
- 205.0

Question 19: A trap primer is:

- the solvent used to clean ABS pipe before final gluing
- the solvent used on PEX prior to assembly to a trap
- the solvent used to clean CPCV prior to final gluing as a trap
- a device and system of piping that maintains a water seal in a remote trap
- none of the answers provided

Question 20: The correct reference for the above question is:

- 216.0
- 220.0
- 221.0
- 215.0
- 222.0

Question 21: A vertical pipe is:

- a pipe that is not more than 90 degrees from a vertical position
- a pipe that is not more than 66-2/3 degrees from a vertical position
- a pipe that is not more than 60 degrees from a vertical position
- a pipe that is not more than 45 degrees from a vertical position
- a pipe that is only in a vertical position

Question 22: The correct reference for the above question is:

- 224.0
- 220.0
- 211.0
- 215.0
- 205.0

Question 23: A waste pipe conveys:

- only liquid waste
- liquid waste that may contain fecal matter
- only liquid waste containing fecal matter
- waste from a macerating toilet system
- stormwater and building sewer waste

Question 24: The correct reference for the above question is:

- 224.0
- 220.0
- 211.0
- 215.0
- 225.0

Quiz 3

Question 1: On an installation, the waste line is discovered to have a small crack. What action must the plumber take?

- remove the bad section and replace with new
- seal minor leak with epoxy
- braze crack shut
- weld crack shut
- do nothing until the crack starts to leak

Question 2: The correct reference for the above question is:

- 310.1
- 310.2
- 311.2
- 311.8

Question 3: The minimum sized cast iron pipe that can be threaded is:

- 2 inches
- 3 inches
- 4 inches
- 6 inches
- none, code does not allow threading

Question 4: The correct reference for the above question is:

- 310.1
- 310.2
- 311.2
- 311.8
- Not referenced

Question 5: A building sewer line must be installed at least _____ from the building.

- 1/2 ft.
- 1 ft.
- 16 inches
- 24 inches
- no minimum distance

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

Question 6: The correct reference for the above question is:

- 313.1
- 313.2
- 313.3
- 313.4
- 313.5

Question 7: Piping penetrations through a floor must be:

- sealed
- fire-stopped
- waterproofed
- fire-stopped only if penetrating a fire-resistant-rated floor
- followed by the building code

Question 8: The correct reference for the above question is:

- 313.1
- 313.2
- 313.3
- 313.5
- 313.7

Question 9: All piping shall be supported in such a manner as to maintain its alignment and prevent sagging.

- Yes
- No

Question 10: The correct reference for the above question is:

- 314.1
- 314.2
- 314.3
- 314.4

Question 11: When rat-proofing a drain, a strainer plate must have an opening no larger than:

- 1/8 inch
- 1/4 inch
- 3/8 inch
- 1/2 inch
- 5/8 inch

Question 12: The correct reference for the above question is:

- 313.12.1
- 313.12.2
- 313.12.3
- 313.12.4

Question 13: The minimum size of a hanger rod supporting 10" pipe is:

- 3/8 inch
- 1/2 inch
- 5/8 inch
- any of the answers provided
- none of the answers provided

Question 14: The correct reference for the above question is:

- Table 3-1
- Table 3-2
- Table 4-1
- Table 5-1

Question 15: The minimum distance between hanger supports when hanging 1" steel thread pipe for gas shall be:

- 4 ft.
- 8 ft.
- 10 ft.
- 12 ft.
- 16 ft.

Question 16: The correct reference for the above question is:

- Table 3-1
- Table 3-2
- Table 4-1
- Table 5-1

Question 17: When can a restaurant's employees place food and drinks in a storage area which has soil or drain pipes located overhead?

- never
- when the drain pipes have the least number of possible joints
- when drains are equipped with integral seepage pans
- when piping is tested to 25 ft. of water
- all of the answers provided

Question 18: The correct reference for the above question is:

- 316.1
- 317.2
- 318.0
- 319.4

Question 19: Heat fusion welding of thermoplastic pipe or fitting is acceptable.

- True
- False

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

Question 20: The correct reference for the above question is:

- 316.1.11
- 316.2
- 316.1.6
- 317.1.11

Quiz 4

Question 1: A new toilet in a residential application must meet water consumption standards. The maximum amount of water per flush shall not exceed _____.

- 1.0 gal
- 1.6 gal
- 2.1 gal
- 3.5 gal
- 5.0 gal

Question 2: The correct reference for the above question is:

- 401
- 402
- 403
- 404

Question 3: A urinal shall not exceed _____ gallons per flush.

- 1.0
- 0.8
- 0.7
- 0.6
- 0.5

Question 4: The correct reference section for the above question is:

- 400
- 401
- 402
- 403

Question 5: Tanks flushing more than ____ urinal(s) shall be automatic in operation, and of sufficient capacity to provide the necessary volume to flush and properly cleanse all urinals simultaneously.

- 1
- 2
- 3
- 4

Question 6: The correct reference for the above question is:

- 410.1
- 410.2

- 410.3
- 410.4

Question 7: The overflow pipe from a fixture shall be connected on the house or inlet side of the fixture trap.

- True
- False

Question 8: The correct reference for the above question is:

- 402.0
- 403.0
- 404.0
- 405.0

Question 9: When is a strainer on a plumbing fixture NOT required?

- on a urinal
- on a residential sink
- on a commercial sink
- on a bathtub
- on a shower

Question 10: The correct reference for the above question is:

- 404.1
- 404.2
- 404.3
- 404.4

Question 11: A dishwasher drain may be connected to the discharge side of a food waste disposal unit.

- True
- False

Question 12: The correct reference for the above question is:

- 404.1
- 404.2
- 404.3
- 404.4

Question 13: A drinking fountain shall not be installed _____.

- in a public toilet room
- in a shower room
- in a gymnasium locker room
- in a steam bath

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

Question 14: The correct reference for the above question is:

- 405.1
- 405.2
- 405.3
- 405.4

Question 15: Sheet metal restaurant sinks shall be a minimum gauge thickness of_____.

- 12
- 14
- 16
- 20
- 24

Question 16: The correct reference for the above question is:

- 406.1
- 406.2
- 406.3
- 406.4

Question 17: When installing a toilet, it shall not be closer than ____ from its center line to a side wall.

- 12 inches
- 15 inches
- 16 inches
- 18 inches
- 24 inches.

Question 18: The correct reference for the above question is:

- 405
- 406
- 407
- 408

Question 19: When installing a toilet, it shall not be closer than ____ from its center line to the center line of an adjacent toilet.

- 12 inches
- 16 inches
- 18 inches
- 24 inches
- 30 inches

Question 20: The correct reference for the above question is:

- 405
- 406
- 407
- 408

Question 21: The clear space in front of a toilet needs to be at least _____ inches.

- 12
- 16
- 22
- 30
- none of the answers provided

Question 22: The correct reference for the above question is:

- 405
- 406
- 407
- 408

Question 23: In a public restroom that has 1 water closet and 1 urinal, a floor drain must be installed.

- True
- False

Question 24: The correct reference for the above question is:

- 408.0
- 409.5
- 410.6
- 411.2

Question 25: A shower is to have a minimum interior area of at least _____ sq. inches.

- 800
- 1200
- 1444
- 1556
- none of the answers provided

Question 26: The correct reference for the above question is:

- 408.0
- 409.5
- 410.6
- 411.7

Question 27: The location of the shower valves and heads:

- must be on the side wall
- can be adjusted prior to stepping into the shower spray
- must be placed so that the shower head does not discharge at the entrance to the compartment
- none of the answers provided
- all of the answers provided

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

Question 28: The correct reference for the above question is:

- 408.0
- 409.5
- 410.6
- 411.10

Question 29: In a public restroom the maximum water temperature shall not exceed _____ degrees F.

- 110
- 115
- 120
- 125
- 140

Question 30: The correct reference for the above question is:

- 413.0
- 414.5
- 415.1
- 417.2

Question 31: When installing a sink that has 2 handles to control the water flow, the _____ side shall be hot water and the _____ side shall be cold water (when facing the sink).

- left / right
- right / left
- either side
- not addressed in the code

Question 32: The correct reference for the above question is:

- 413.1
- 414.0
- 415.0
- 416.0

Question 33: The maximum temperature of hot water discharging into the bathtub filler shall be _____ degrees F.

- 110
- 115
- 120
- 125
- 140

Question 34: The correct reference for the above question is:

- 414.3
- 414.4
- 414.5
- 415.0

Quiz 5

Question 1: A hot water tank is to be installed in a 3 bedroom, 3 bath house. The first hour rating of the tank shall be at least _____ gallons.

- 42
- 54
- 67
- 80

Question 2: The correct reference for the above question is:

- 501.0
- 502.1
- 502.5
- 502.12

Question 3: A hot water tank is to be installed in a 3 bedroom, 1.5 bath house. The first hour rating of the tank shall be at least _____ gallons.

- 42
- 54
- 67
- 80

Question 4: The correct reference for the above question is:

- 501.0
- 502.1
- 502.5
- 502.12

Question 5: A hot water tank is to be installed in a 4 bedroom, 2.5 bath house. The first hour rating of the tank shall be at least _____ gallons.

- 42
- 54
- 67
- 80

Question 6: The correct reference for the above question is:

- 501.0
- 502.1
- 502.5
- 502.12

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

Question 7: A fuel-burning water heater installed in a closet of a bedroom or bathroom is not allowed unless all of the following are true EXCEPT

- when it is a direct vent type
- when the closet door is gasketed
- when the closet door has a self-closing device
- when the closet door has a bolting lock

Question 8: The correct reference for the above question is:

- 505.1
- 505.3
- 505.4
- 506.1

Question 9: A shut-off valve may be placed between the water tank and pressure relief valve.

- True
- False

Question 10: The correct reference for the above question is:

- 505.1
- 505.3
- 505.4
- 505.6

Question 11: A shut-off valve may be placed between the pressure relief valve and discharge piping to atmosphere.

- True
- False

Question 12: The correct reference for the above question is:

- 505.1
- 505.3
- 505.4
- 505.6

Question 13: In seismic areas C-F, a water heater must be strapped to resist horizontal displacement.

- 1/4, 1/4, 4
- 1/4, 1/4, 6
- 1/3, 1/3, 4
- 1/3, 1/3, 6

Question 14: The correct reference for the above question is:

- 508.1

- 508.2
- 508.3
- 508.4

Question 15: A water heater installed in an attic shall have a waterproof drain with a minimum _____ inch drain line.

- 1/2
- 3/4
- 1
- 1-1/2
- not addressed in the code since water heaters in attics are not allowed

Question 16: The correct reference for the above question is:

- 508.1
- 508.2
- 508.3
- 508.4

Question 17: The discharge from a relief valve may empty into a water heater pan.

- True
- False

Question 18: The correct reference for the above question is:

- 508.1
- 508.2
- 508.3
- 508.4
- 508.5

Question 19: When is a non-direct-vent water heater allowed in a facility that routinely uses flammable aerosol sprays?

- never—no exceptions
- always—no restrictions
- when the tank is 40 gallons or less
- when the tank has a flame guard burner
- none of the answers provided

Question 20: The correct reference for the above question is:

- 508.10
- 508.2
- 508.3
- 508.4
- 508.5

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

Question 21: When installing a gas water heater in a residential garage, the tank must be at least _____ inches above the floor unless _____.

- 16, no exceptions
- 18, no exceptions
- 16, listed as flammable vapor ignition resistant
- 18, listed as flammable vapor ignition resistant
- 24, listed as flammable vapor ignition resistant

Question 22: The correct reference for the above question is:

- 508.11
- 508.12
- 508.13
- 508.14
- 508.20

Quiz 6

Question 1: Water closets and urinals shall be flushed by means of an approved _____.

- flush tank
- flushometer valve
- both of the answers provided
- neither of the answers provided

Question 2: The correct reference for the above question is:

- 601.1
- 602.1
- 603.3
- 604.5

Question 3: Potable water systems shall be marked with signage/labels that have _____.

- green background and white lettering
- yellow background and black lettering
- purple background and black lettering
- orange background and white lettering
- light blue background and black lettering

Question 4: The correct reference for the above question is:

- 600.0
- 601.2
- 601.3
- 602.4

Question 5: Non-potable water systems shall be marked with signage/labels that have _____.

- green background and white lettering
- yellow background and black lettering
- purple background and black lettering
- orange background and white lettering
- light blue background and black lettering

Question 6: The correct reference for the above question is:

- 600.0
- 601.2
- 601.3
- 602.4

Question 7: Reclaimed water systems shall be marked with signage/labels that have _____.

- green background and white lettering
- yellow background and black lettering
- purple background and black lettering
- orange background and white lettering
- light blue background and black lettering

Question 8: The correct reference for the above question is:

- 600.0
- 601.2
- 601.3
- 602.4

Question 9: The minimum airgap for a water distribution system with an effective opening not greater than one (1) inch in diameter, when affected by sidewalls, is _____ inches.

- 1
- 1-1/2
- 2
- 2-1/4
- 3

Question 10: The correct reference for the above question is:

- Table 6-1
- Table 6-2
- Table 6-3
- Table 6-4

Question 11: Potable water supply to carbonators shall be protected by either an airgap or a vented backflow preventer for carbonated beverage dispensers installed within the carbonated beverage dispenser.

- True
- False

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

Question 12: The correct reference for the above question is:

- 603.1
- 603.2
- 603.3
- 603.4.12

Question 13: A heat exchanger on a solar water heater using glycol shall be:

- single walled
- double walled
- triple walled
- not addressed in the code

Question 14: The correct reference for the above question is:

- 603.1
- 603.2
- 603.3
- 603.4.4.1

Question 15: The minimum weight of copper tubing for water lines below ground is:

- type K
- type L
- type M
- Schedule 40
- Schedule 80

Question 16: The correct reference for the above question is:

- 603.1
- 604.2
- 604.3
- 604.6

Question 17: A control valve shall be installed immediately ahead of each water-supplied appliance.

- True
- False

Question 18: The correct reference for the above question is:

- 603.1
- 604.2
- 604.3
- 605.5

Question 19: Where local static water pressure is above _____ psig, a pressure regulator shall be installed.

- 50
- 60

- 70
- 80
- 100

Question 20: The correct reference for the above question is:

- 608.1
- 608.2
- 608.3
- 608.4
- 608.7

Question 21: Pressure relief valves shall not be set above _____ psig.

- 150
- 160
- 170
- 180
- 200

Question 22: The correct reference for the above question is:

- 608.1
- 608.2
- 608.3
- 608.4
- 608.7

Question 23: A water pipe may be laid in the same trench with a clay sewer line if _____.

- the water pipe is 1" galvanized steel
- the clay sewer line is 3"
- the water pipe is at least 12" above the top of the sewer line and placed on a solid shelf excavated 12" horizontally from the sewer line
- no special precautions are needed
- never allowed

Question 24: The correct reference for the above question is:

- 608.2
- 609.2
- 609.6
- 609.10

2009 UPC Chapters 2-6 Questions

RV 11.14.2014

Question 25: Unions should be installed in the water supply piping within _____ inches of equipment which may require removal or replacement.

- 6
- 12
- 16
- 24
- 36

Question 26: The correct reference for the above question is:

- 608.2
- 609.5
- 609.6
- 609.10

Question 27: Which of the following is NOT used in sizing water supply systems?

- number of equivalent fixture units
- maximum pressure available
- difference in elevation between the meter and the highest outlet
- length of supply pipe from the meter to the most remote outlet

Question 28: The correct reference for the above question is:

- 610.2
- 610.5
- 610.7
- 610.8
- 610.12